

imagePROGRAF TA-30

QUIET, COMPACT, AND VERSATILE MULTI-PURPOSE PRINTER

A compact and quiet multi-purpose device with high-level technology – designed for the low-volume print requirements of offices, schools and retail.



- **Save space**
Small and light, the compact design fits flush against the wall, with full front accessibility
- **Boost productivity**
Maintain speed and reduce costs with continuous printing, even during ink tank replacement
- **Precision print**
Innovative Air Feeding System keeps paper flat for high quality printing on a variety of media
- **Office friendly**
Quiet operation and printing at fast speeds combined with ease of use operation
- **LUCIA TD pigment ink**
Make the printed surface smooth with crisp lines and sharp texts for graphics and posters

PRODUCT RANGE



imagePROGRAF TA-20



imagePROGRAF TA-30



imagePROGRAF TM-300

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TA-30

TECHNOLOGY

Printer Type	5 colors 36"/914mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Print Resolution	2,400 x 1,200 dpi
Number of Nozzles	15,360 nozzles (MBK 5,120 nozzles, Other Colors 2,560 nozzles each)
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
Nozzle Pitch	1,200dpi (2 lines)
Ink Droplet Size	minimum 5 pl per colour
Ink Capacity	Sales Ink: 55ml Bundled Starter Ink: 55ml (2 x MBK, 1 x BK,C,M,Y)
Ink Type	Pigment inks - Matte Black, Black, Cyan, Magenta, Yellow
OS Compatibility	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10 Microsoft Windows 64 Bit: Windows 7, 8.1, 10, Windows Server 2008R2, Windows Server 2012/2012R2, Windows Server 2016, Windows Server 2019 Apple Macintosh: OS X 10.10.5-OS X 10.11, macOS 10.12- macOS 10.15
Printer Languages	SG Raster (Swift Graphic Raster),HP-GL/2, HP RTL, JPEG (Ver. JFIF1.02)
Standard Interfaces	USB B Port: Hi-Speed Ethernet: IEEE 802.3 10base-T/IEEE 802.3u 100base-TX/IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b * Please refer to user manual how to activate /deactivate the wireless LAN

MEMORY

Standard memory	2 GB
Hard Drive	NO

PRINT TIME FOR A1 PAGE SIZE

Media Type		Print Mode	Print Time
CAD Drawing		Fast	00:53 min
Plain Paper (A0 size Portrait)		Standard	01:34 min
Poster		Print Mode	Print Time
Plain Paper (A0 size Portrait)		Fast	00:50 min
		Standard	01:25 min
Heavy Coated Paper (A0 paper size)		Print Mode	Print Time
		Fast	01:44 min
		Standard	03:10 min

MEDIA HANDLING

Media Feed and Output	Roll Paper: One Roll, Upper-loading, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 203.2 -917 mm Cut sheet: 210 - 431.8 mm
Media Thickness	Roll/Cut: 0.07 - 0.8 mm
Minimum Printable Length	Roll paper: 203.2 mm Cut sheet: 279.4 mm
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 594mm
Maximum Media Roll Diameter	150 mm or less
Media Core Size	Internal diameter of roll core: 2"/3"(option)
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins Printable area

Media Feed Capacity	Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm Manually switchable by user
Media Take-up roll unit	N/A
Borderless Printing Width (Roll Only)	(Printable) 203.2-917mm *Roll paper only * No size restriction
Maximum number of delivered prints	Standard position: 1 sheet

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)	1289 x 870 x 1059 mm (Basket Open) 1289 x 757 x 1059 mm (Basket Closed) 53 kg (Including Roll Holder Set and Roll unit, excluding ink and print head)
Packaged Dimensions WxDxH (mm) and Weight (Kg)	Printer (Main unit with pallet): 1492 x 909 x 685 mm 74 kg Stand+ Basket (SD-33): 1362 x 824 x 268 mm 17 kg

POWER AND OPERATING REQUIREMENTS

Power Supply	AC 100-240V (50-60Hz)
Power Consumption	Operation: 59 W or less Sleep mode: 3.6W or less Default setting for the time to enter the Sleep mode: approx. 5 mins Power off: 0.3 W or less

Operating Environment

Acoustic Noise (Power/Pressure)	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation) Operation: 42 dB (A) (Plain paper, line drawing, standard mode) Standby: 35dB (A) or less Operation: 5.8 Bels (Plain paper, line drawing, standard mode) (Measured on ISO 7779 standard and described based on ISO9296 standard)
--	---

Regulations Certificates

WHAT'S INCLUDED

What's in the Box?	Printer, 1 print head, Power Cabel, 1 set of starter ink tanks, Set up guide, Quick Guide, Safety/Standard Environment leaflet, User Software CD-ROM (Win), EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet
---------------------------	--

Software Included

	imagePROGRAF TA- Unified Printer Driver, Other software available as Download from Web.
--	--

OPTIONS

Optional Items	2/3" Roll Holder: RH2-35
-----------------------	--------------------------

CONSUMABLES

User Replaceable Items	Ink Tank: PFI-030 (55ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31
-------------------------------	--

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2019